

TC2000-G1/G2/G3

Thermal Cycler Gradient



- TC2000-G1/G2/G3 is an indispensable laboratory instrument in the field of molecular biology, which can be used for gene sequencing, gene cloning, gene expression, mutation, and plays an important role in various fields such as agriculture, food testing, environmental science, drug development and so on.

Feature:

- 10-inch large screen new UI interface, divided into single-channel / dual-channel / three-channel, to meet different experimental requirements.
- With advanced gradient temperature control technology, high-performance and long-lasting Peltier refrigeration and heating, which can achieve precise temperature control in zones.
- Multi-channel module design, can run several different PCR gradient programs at the same time, to achieve multi-purpose machine.
- Self-adaptive pressure lever hot cap, close and tighten the cap in one step, can be adapted to different heights of test tubes.
- Supports up to 199 cycles to perform the next operation, and runs a countdown disc to visually display the remaining time.
- Edge temperature compensation technology for good temperature uniformity and gradient settings for easy optimisation of experimental conditions.
- Real-time display of the running status of the programme, you can set the security account and password according to customer demand.
- Automatic power failure protection, automatically execute unfinished cycles after power restoration to ensure the safe operation of the whole amplification process.
- Hot lid temperature and hot lid operating mode can be set to meet different experimental application requirements.
- USB interface, support for U-disk storage/reading PCR data, support for U-disk software update, can be customised to meet the function of multiple file storage, support for Touch down PCR and Long PCR experiments.
- Compatible with common 0.2mL PCR tubes, PCR-8 Strips and 96-well PCR plates (no skirt, full skirt, half skirt).

Technical Parameters:

Model	TC 2000- G1	TC 2000- G2	TC 2000- G3
Sample Capacity	96×0.2mL PCR tube 12× PCR-8 strips 96 PCR Microplate	96×0.2mL PCR 12×PCR-8 strips	96×0.2mL PCR 12×PCR-8 strips
Module	1×96	2×48	3×32
Heating Temperature Range / °C	0-105	0-105	0-105
Lid Temperature Range / °C	30-115	30-115	30-115
Temperature Display / °C	0.1	0.1	0.1
Temp Control Accuracy / °C	±0.1	±0.1	±0.1
Temperature uniformity @55 °C	±0.2	±0.2	±0.2
Max. Heating/Cooling Rate	5° C/Sec	5° C/Sec	5° C/Sec
Gradient Temp. Setting Range / °C	30-105	30-105	30-105
Gradient Range / °C	1-42, enter 0 to turn off the gradient.	1-25, enter 0 to turn off the gradient.	1-25, enter 0 to turn off the gradient.
Temperature Control Method	Block/Tube	Block/Tube	Block/Tube
Adapter Block Material	Aluminum	Aluminum	Aluminum
Display	10" LCD 1280×800	10" LCD 1280×800	10" LCD 1280×800
Input	Touchpanel	Touch panel	Touch panel
Power Off Protection	Yes	Yes	Yes
Skip to The Next Step	Yes	Yes	Yes
Communication Interface	USB2.0, WIFI	USB2.0, WIFI	USB2.0, WIFI
Number of Program Stores	20000+ (USB FLASH)	20000+ (USB FLASH)	20000+ (USB FLASH)
User Defined File System	Up to 30 steps and 199 cycle in a single program		
Power Supply	100-240V, 50/60HZ, 600W		
Dimension [W×D×H]	422×310×264mm	422×310×261mm	422×310×252mm
Weight	11kg	11kg	11kg