FSF-5V416 2~8℃ Pharmacy Refrigerator

FSF-5V416 2~8℃ Pharmacy Refrigerator (416 liter) is widely used in hospitals pharmacy stores and laboratories. This is for placing and preserving storage such as drugs, vaccines, enzymes, hormones, stem cells, extracted RNA and gene libraries and important biological and chemical reagents.

Features

- Fast pull down: Real forced air cooling system
- Temperature simulation box: Accurately detect the temperature of storage
- Suction circulation system: Big fans with less temp. flutuation & better uniformity
- Universal castor wheels: Proven heavy-duty lockable castors
- Lockable doors: Standard locks with keys
- High-quality steel materials: Antibacterial and corrosion resistant
- Precise temp. Control: Temp. control accurate to 0.1C
- 5 types of alarm : Audible and visual alarms
- Variable space: Height adjustable shelves
- Eco-friendly: CFC-free refrigerant and energy-saving



Structure

- High-precision control system
- LED lighting
- Big Suction fan
- Temperature simulation box
- Standard Lock & key
- Lockable castors
- Leveling feet
- Heating double-layer glass
- High/low temp. Alarm
- Power failure alarm
- Door ajar alarm
- Thermostat failure alarm

Optional Accessories

- USB interface
- Data logger

Technical Parameter

Performance		Refrigeration System		Alarms	
Cooling method	Forced Air Cooling	Refrigerant	R290	High/low temperature	Y
Defrost	Auto	Temp. controller	Microprocessor	Power failure	Y
Shelf/drawer	Shelves/5	Sensor	NTC	Sensor error	Y
Temperature range	2℃～8℃	Display	LED Digital display	Door ajar	Y
Ambient temperature	10~32℃	External material	SPCC sprayed steel	Controller failure	Y
Noise(db)	50	Internal material	SPCC sprayed steel	Power failure alarm(For controller)	8 h
Capacity	416/14.69	Compressor	1		

Electrical Data		Dimensions		Other	
Voltage frequency	220V 50/60Hz or 110V/60Hz	Package size(W*D*H)	785*552*1927(mm)	Door Type	Heated Glass door
Power(W)	330W	Exterior size(W*D*H)	685*429*1380(mm)	Remote alram pore	yes
Current(A)	1.85A	Interior size(W*D*H)	868*660*2060(mm)	USB port	Optional
Power consumption	3.98 kWh/24h	NW/GW(kg)	120/156	Access port QTY/Dia.	1/25mm