

GT 116C High Speed Table Centrifuge

• Technical Parameter

Model	GT116C
Max Speed	16500rpm
Max RCF	21615xg
Max Capacity	12*5ml
Timer	1s~99h59min59s
Revolutions/min	±10r/min
Voltage	AC 220±22V 50Hz 10A
Power	350W
Noise Level	≤ 62dB (A)
Size	270×390×240 (mm)
Net Weight	21kg



• Optional Rotor

Angle rotor			
No	Capacity(ml)	Max Speed (r/min)	Max RCF(xg)
1	16×1.5/2.0ml	16500rpm	20880xg
2	12×5ml	16000rpm	17344xg
3	24×1.5/2.0ml	15000rpm	21615xg
4	4×8×0.2ml PCR Row	15000rpm	14866xg
5	8×8×0.2ml PCR Row	14000rpm	15032xg
6	Capillary rotor 24 hole	12000rpm	13845xg

Note: If you have other needs, please contact us

GTR 116C High Speed Table Refrigerated Centrifuge

• Technical Parameter

Model	GTR116C
Max Speed	16500rpm
Max RCF	21615xg
Max Capacity	12×5ml
Timer	1s~99h59min59s
Revolutions/min	±10r/min
Temp Range	-20°C ~ 40°C
Temp Accuracy	±1.0°C
Voltage	AC 220±22V 50Hz 10A
Power	550W
Noise Level	≤ 60dB (A)
Size	315×475×310 (mm)
Net Weight	38kg
Rotor automatic identification	No



• Optional Rotor

Angle rotor			
No	Capacity(ml)	Max Speed (r/min)	Max RCF(xg)
1	16×1.5/2.0ml	16500rpm	20880xg
2	12×5ml	16000rpm	17344xg
3	24×1.5/2.0ml	15000rpm	21615xg
4	4×8×0.2ml PCRRow	15000rpm	14866xg
5	8×8×0.2ml PCRRow	14000rpm	15032xg
6	Capillary rotor 24 hole	12000rpm	13845xg

Note: If you have other needs, please contact us