

HB100-Pro Circular Heating Block

Feature

- Fast heating: The room temperature rises to 100℃ for less than 10 minutes
- Small size: compact internal structure, smaller footprint
- Accurate temperature control: Temperature control accuracy <1℃
- Dual display option: set temperature main display, time main display
- Multiple module options: 6 heating modules can be selected, with tightly arranged holes to accommodate more samples
- Compatible containers: 0.2mL, 0.5mL, 1.5mL, 2mL, 5mL



Technical Parameters

Model	HB100-Pro
Temperature Display	Temperature display
Temperature Control Range [℃]	Room temperature - 100℃
Temperature Display Error	±0.5℃
Temperature Stability @ 37℃	±0.3
Timing Range	0-99h59min
Allow Relative Humidity	<80%
Input Power Supply	100-120V, 50/60Hz 200-220V, 50/60Hz
Dimensions [length x width x height]	210×180×130mm
Weight [kg]	0.9kg

Cat.No.18901479		Cat.No.18901477	
Circular heating module (18X5mL)		Circular heating module (59X0.5mL)	
Cat.No.18901478		Cat.No.18901476	
Circular heating module (96X0.2mL)		Circular heating module (39X1.5mL)	
Cat.No.18901480		Cat.No.18901704	
Circular heating module (24X0.5mL+30x1.5mL)		Circular heating module 39X2mL)	