Pulsating Vacuum Vertical Steam Sterilizer

-Touch Screen Display (3-Times pre-vacuum)

Production Introduces

- Hand wheel translation and quick opening structure;
- Three times pre-vacuum, high quality stainless steel material;
- Microcomputer automatic control, arbitrary setting sterilization parameters;
- Safety interlocking device;
- LED touch screen display,standard test interface;
- Self-expanding seal;
- With drying function;
- With stainless steel bucket or basket;
- With automatic protection function:over temperature protection; over pressure self discharge protection;low water level protection; anti dry burning;
- Automatic water;
- External steam generator;
- Buzzer reminder after sterilization, automatic stop;
- Automatic discharge of cold air, automatic steam exhaust after sterilization Internal printer.



Technical Parameter

Model	FSF-35M	FSF-50M	FSF-75M	FSF-100M
Volume	35L	50L	75L	100L
Power	3.5kW	3.5kW	4.5kW	4.5kW
Voltage	AC220V/50HZ			
Design Pressure	0.25MPa			
Design Temperature	139℃			
Rated Working Pressure	0.22MPa			
Rated Working Temperature	134℃			
Sterilization Temperature Setting Range	116℃-134℃			
Sterilization Time Setting Range	4-120min			
Drying Time Setting Range	0-240min			
Chamber Size (mm)	Φ350x400	Φ400x505	Φ400x655	Φ450x650
Bucket Dimension(mm)	Φ330x320	Φ380x430	Φ380x560	Φ420x540
Basket Dimension(mm)(Option)	Φ320x350	Φ360x280x1	Φ360x280x2	Φ410x300x2
Outer Dimension(mm)	698x498x940	630x500x1180	725x525x1170	760x560x1260
Packing Size (L x W x H)(mm)	790x610x1130	800x600x1230	840x610x1310	870x650x1380
Gross/Net Weight	125/110kg	136/116kg	141/121kg	180/146kg