Vertical Pressure Steam Sterilizer

Used to medical and health undertakings,scientific research,agriculture and other units,medical equipment,dressing glassware,solution medium disinfection and sterilization.



Production Introduces

- Fully stainless steel structure.
- Hand wheel type of quick-open door structure.
- LCD display of working status,touch type key.
- Door safety lock system.
- Self-inflating type seal.
- Over temperature&over pressure auto-protection.
- Safe protection of water lacking.
- Automatically shut off with beep reminding after sterilization.
- With two stainless steel sterilizing baskets.
- A high efficiency filter is added to the exhaust.

Technical Parameter

Model	FSF-35HG	FSF-50HG	FSF-75HG	FSF-100HG
Chamber Volume	35L Φ318*415mm	50L Φ340*550mm	75L Φ400*600mm	100L Φ440*650mm
Design Pressure	0.3Mpa			
Design Temperature	150℃			
Max.Working Temperature	138℃			
Max.Working Pressure	0.25MPa			
Timer Range	0-99min or 0-99h 59 min			
Power	1*2.5KW/AC 220V.50HZ	2*1.5KW/AC 220V.50HZ	3*1.5KW/AC 220V.50HZ	
Overall Dimension(mm)	710*490*1150	710*490*1150	750*510*1250	750*510*1250
Transport Dimension(mm)	740*550*1310	740*550*1310	780*600*1420	780*600*1420
G.W/N.W(kg)	120/95	124/100	137/111	155/129